



Super B Lithium batteries to perform better







## SB12V20P-FC

Lightweight Lithium Ion starter battery, 7.05 lb / 3.2 kg kilogram, specially developed for Racing cars up to 4 Litre using alternator.

### Safety

super B batteries are based on Lithium Iron Phosphate technology (LiFePO4). This so called Lithium Ion technology as used in the super B batteries is the safest Lithium Ion technology today. On top of that our specially designed casing and electronics further increase safety and durability.

-  **Recharges much faster**
-  **Longer service life**
-  **Incredible small size**
-  **Weighs less**
-  **Low self discharge**

## Applications for SB12V20P-FC

DTM	Group C	WRC
BTCC	WTCC	NASCAR
LMS	GT's	GT Endurance
Dakar Rally Raid	Britsports	ALMS
4x4		

Super B Lithium batteries to perform better

Diamantstraat 1e  
7554 TA Hengelo  
The Netherlands

T +31 (0)748200010  
F +31 (0)74 8200011  
E [info@super-b.com](mailto:info@super-b.com)



## Technical specifications SB12V20P-FC

SKU/EAN13	8718531360051
Battery Designation	4IFP83/121/239-8
Height (mm)	237,50 / 238,50
Diameter (mm)	NA
Width (mm)	119,50 / 120,50
Thickness (mm)	81,50 / 82,50
Nominal voltage (V)	13,2V
Charge method	CCCV
End of charge voltage (V)	15,2V
End of charge voltage (V) for endurance (cycle life)	14,4V
Charge current (A)	80A (4C)
Charge current (A) for endurance (cycle life)	24A (1C)
End-of-discharge voltage (V)	8V
?End-of-discharge voltage (V) for endurance (cycle life)	10V
Discharge current (A)	560A (30C)
Discharge current (A) for endurance (cycle life)	18,4A (1C)
Discharge pulse current (A) (10 seconds)	960A (52C)
Discharge pulse current (A) (1 second)	1200A (65C)
Discharge performance at 20 °C (rated capacity)	18,4Ah / 242,88Wh
Discharge performance at -20 °C (capacity)	16,56Ah / 218,592Wh
High rate discharge performance at 20 °C (capacity)	17,48Ah / 230,736Wh
Weight	3,2kg