



Super B Lithium batteries to perform better








SB12V20P-SC

Lightweight Lithium Ion starter battery, 7.94 lb / 3.6 kg, specially developed for racing cars up to 4 litre using alternator.

Safety

super B batteries are based on Lithium Iron Phosphate technology (LiFePO₄). This Lithium Ion technology used in super B batteries is the safest Lithium Ion technology available today. On top of that our bespoke casing and electronics further increase safety and durability.

-  **Recharges much faster**
-  **Longer service life**
-  **Incredible small size**
-  **Weighs less**
-  **Low self discharge**

Applications for SB12V20P-SC

DTM	Group C	WRC
BTCC	WTCC	NASCAR
LMS	GT's	GT Endurance
Dakar Rally Raid	Britsports	ALMS
4x4		

Super B Lithium batteries to perform better

Diamantstraat 1e
7554 TA Hengelo
The Netherlands

T +31 (0)748200010
F +31 (0)74 8200011
E info@super-b.com



Technical specifications SB12V20P-SC

SKU/EAN13	8718531360075
Battery Designation	4IFP97/250/142-8
Height (mm)	140,30 / 141,30
Diameter (mm)	NA
Width (mm)	248,35 / 249,35
Thickness (mm)	95,25 / 96,25
Nominal voltage (V)	13,2V
Charge method	CCCV
End of charge voltage (V)	15,2V
End of charge voltage (V) for endurance (cycle life)	14,4V
Charge current (A)	80A (4C)
Charge current (A) for endurance (cycle life)	24A (1C)
End-of-discharge voltage (V)	8V
?End-of-discharge voltage (V) for endurance (cycle life)	10V
Discharge current (A)	560A (30C)
Discharge current (A) for endurance (cycle life)	18,4A (1C)
Discharge pulse current (A) (10 seconds)	960A (52C)
Discharge pulse current (A) (1 second)	1200A (65C)
Discharge performance at 20 °C (rated capacity)	18,4Ah / 242,88Wh
Discharge performance at -20 °C (capacity)	16,56Ah / 218,592Wh
High rate discharge performance at 20 °C (capacity)	17,48Ah / 230,736Wh
Weight	3,6kg